




Position	Qty.	Description	Single Price
	1	<p><b>UP 20-30 N 150</b></p>  <p><b>Note! Product picture may differ from actual product</b></p> <p>Product No.: 59643500            The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump is characterized by:</p> <ul style="list-style-type: none"> <li>* Ceramic shaft and radial bearings.</li> <li>* Carbon axial bearing.</li> <li>* Stainless steel rotor can and bearing plate.</li> <li>* Corrosion-resistant impeller, Composite, PES/PP.</li> <li>* Stainless steel pump housing.</li> </ul> <p>The motor is a 1-phase motor.            No additional motor protection is required.</p> <p><b>Liquid:</b>            Liquid temperature range: 2 .. 110 °C            Liquid temp: 20 °C            Density: 998.2 kg/m<sup>3</sup></p> <p><b>Technical:</b>            Actual calculated flow: 1.48 m<sup>3</sup>/h            Resulting head of the pump: 1.76 m            TF class: 110            Maximum operating pressure: 10 bar            Approvals on nameplate: VDE,GS,CE</p> <p><b>Materials:</b>            Pump housing: Stainless steel                              DIN W.-Nr. 1.4301                              AISI 304            Impeller: Composite, PES/PP</p> <p><b>Installation:</b>            Amb. max at 80 dgr C liquid: 80 °C            Maximum operating pressure: 10 bar            Pipe connection: G 1 1/4            Pressure stage: PN 10            Port-to-port length: 150 mm</p> <p><b>Electrical data:</b></p>	On request

Position	Qty.	Description	Single Price
		Max. power input: 75 W Mains frequency: 50 Hz Rated voltage: 1 x 230 V Current in speed 3: 0.31 A Capacitor size - run: 2 µF Enclosure class (IEC 34-5): 44 Insulation class (IEC 85): F  Others: Net weight: 2.1 kg Gross weight: 2.3 kg Shipping volume: 0.004 m3	



## 59643500 UP 20-30 N 150 50 Hz

