



GENERIC FITTINGS

Serie 1500CZ

Description

Generic fittings made of anti-dezincification brass (CW602N).

Available raw or chrome plated.



Function

The brass generic fittings are suitable for domestic and commercial plumbing, industrial, agricultural application and generally with every non aggressive fluid. The fittings are also available for solar panel systems.

Technical Features

Maximum temperature:	200°C (110°C for fittings with gasket)
Minimum temperature:	-20°C
Maximum operating pressure:	30 bar (10bar for steam applications and for fittings with gasket)
Threads:	female UNI ISO 228 male UNI ISO 228

Description	Material	Treatment
Body	CW602N - EN12165 brass	*
	or	*
	CW602N - EN12164 brass	-
O-ring	Nitrile rubber NBR	-
Plain gasket	Fiber	-

Some fittings may be supplied in chromplated version (see catalogue for futher details).

Certifications



TIEMME Raccorderie S.p.A.
Via Cavallera 6/A (Loc. Barco) - 25045 Castegnato (Bs) - Italy
Tel +39 030 2142211 R.A. - Fax +39 030 2142206
info@tiemme.com - www.tiemme.com

TIEMME Raccorderie S.p.A. si riserva di apportare modifiche in qualsiasi momento senza preavviso. È vietata qualsiasi forma di riproduzione, se non autorizzata.
TIEMME Raccorderie S.p.A.reserves the right to modify contents inany time without prior advise. Is forbidden any reproduction unless under TIEMME authorization
©TIEMME Raccorderie S.p.A. 1500cz Rev. C 03-22